

TECHNICAL SPECIFICATION

RECOUP DRAIN+ DUO HE

WASTE WATER HEAT RECOVERY FOR SHOWERS



- Double-walled copper horizontal heat exchanger
- Designed for integration in wet room spaces
- Patented heat exchanger with built-in shower trap
- Up to 57% heat recovery efficiency *
- 3 recognised installation methods (System A, B & C)
- Can be incorporated into modular bathrooms
- Quadratto grate or tile grate cover options
- Horizontal and vertical waste connection options
- No planned maintenance
- Easy access for cleaning
- SAP listed, SBEM, BREEAM, DEAP & ETL recognised
- Legionella Control risk assessed

GENERAL DATA

DESCRIPTION	VALUE
Overall unit dimensions	866 x 310 mm
Minimum recess into structural floor	136 mm
Minimum recess from final finished floor level	152 mm
Material - Heat Exchanger	Copper
Shower flow rate range	5 - 12.5 Litres/min
Max. Mains water inlet pressure	10 bar
Min. Mains water inlet pressure	1 bar
Max. Mains water working temp	85 °C
Mains & Preheated water connection	½" male BSP
Waste water connection	40 - 43 mm
Full product weight	21 kg
Water volume - mains water	1.42 Litres


PERFORMANCE & EFFICIENCY

SHOWER FLOW RATE @ 40°C (LITRES/MIN)	DRAIN+ DUO HE EFFICIENCY (RECOVERED ENERGY KW) *		
	SYSTEM A	SYSTEM B	SYSTEM C
5.8	57.4% (6.04)		
9.2	57.3% (9.56)		
11.0	56.7% (11.31)	44.9% (8.96)	49.2% (9.82)
12.5	56.4% (12.79)		


* Based on KIWA test data and PCDB figures for SAP 2012

PRESSURE DROP ON THE MAIN WATER CIRCUIT


SHOWER FLOW RATE @ 40°C (LITRES/MIN)	DRAIN+ DUO HE PRESSURE DROP (BAR)		
	SYSTEM A	SYSTEM B	SYSTEM C
5.8	0.14	0.08	0.06
9.2	0.32	0.20	0.13
12.5	0.54	0.34	0.22



Quadratto grate




Tile grate




The technical drawings illustrate the dimensions and components of the Ecolife 10000 BTU/h unit. The top view shows a rectangular unit with a width of 866mm and a depth of 207mm. The side view shows a height of 207mm, with a top section of 136mm and a bottom section of 152mm. The unit is shown in two orientations: a standard view and a 360° rotation view. The 360° rotation view shows the unit's depth of 310mm and the location of the four leveling feet (labeled 1, 2, 3, and 4). The unit is shown with a finished floor level indicated by a dashed line.

- 1 - RECOUP Drain+ Duo
- 2 - Waste Syphon Ø50mm
- 3 - 50mm to 40 - 43mm reducer



INSTALLATION METHODS




SYSTEM A

Preheated water supplied to shower mixer (cold inlet) and the water heater

This installation method provides the highest WWHRS efficiency.

Only one WWHRS unit can supply preheated water to the water heater as System A. All secondary WWHRS units should be connected as System B.

To maximise SAP impact, install WWHRS as System A on the primary shower, or in a room with a shower only.




SYSTEM B

Preheated water supplied to shower mixer (cold inlet) on the shower only

The WWHRS efficiency of this installation method is not as high as System A or C but is the simplest and often the most cost-effective method to install or retrofit.

As preheated water is supplied to the cold side of the shower TMV only, there is no additional connection to the water heater . System B should be used for any secondary showers in a dwelling or where multiple showers are fed from centralised plant.



SYSTEM C

Preheated water supplied to water heater **only**

Greater WWHRS efficiencies are produced than System B but lower than System A. Only one WWHRS unit can feed preheated water to the water heater as System C.

Combi-Boiler, Cylinder (Any heat source inc. Boiler, Heat Pump, Direct Electric, Solar Thermal), Heat Interface Unit (HIU) or Thermal Store.

- For more detail watch our [installation method animation](#) here.

SPECIFYING - RECOUP DRAIN+ DUO HE

Recoup WWHRS | Drain+ Duo HE | Installed as System A; System B; System C (delete as appropriate) | to (Add shower(s) install location)

Include the line of text above or go to specify.recoup.co.uk for the full Recoup Drain+ Duo HE product specification.